



PART NO. 504 GPS SERIES

SPECIFICATION:

- **PRESSURE:**
Inlet (Operating): 1500 to 3500 PSIG
Proof: 5000 PSIG
Burst: 7500 PSIG (min.)
- **TEMPERATURE RANGE:**
Operating: -65 to +160°F (-54 to +71°C)
- **MEDIUM:**
Dry air and inert gases

CABLE OPERATED BALL VALVE

- **FLOW:**
Equivalent to .160 DIA. orifice
- **LEAKAGE:**
Bubble tight up to maximum operating pressure
- **WEIGHT:**
0.71 lb. (max.) without optional pressure gage (weight depends on model), gage protector shell (.19 lb), and siphon tube (.10 lb)
- **OPERATION:**
To arm: Engage cable ball end in pulley and inert 3/16 hex key in pulley socket. Lift lock pin, rotate pulley counter-clockwise with hex key until pin aligns

with mark ▲, release lock pin. Detent will engage. To actuate: Pull cable. (Max. pull force required is 15 lbs.)

MATERIALS:

Anodized aluminum, stainless steel, soft seat, and Buna-N

APPLICATIONS:

Used when mechanical actuation or initiation of a pressure regulated gas flow is required. Typical applications include rapid inflation of life rafts and emergency slide evacuation systems for military and commercial aircraft.

Note: Other valve configurations with alternate feature orientations available upon request.

